

尺寸 Size:110mmx110mmx25mm

风量 Airflow:70~100m³/hr

41~59CFM

重量 Weight:304g

噪音 Noise:30~41dBA

风叶 Impeller:PBT Thermoplastic Black,UL94-V0

外框 Frame:Aluminum Alloy

端子 Terminals: 0.5mm


引线 Lead Wire:AWG#22 UL 1007

(Optional)

马达 Motor:Shaded Pole Induction Motor

安规认证 Safety:CE> ©

温度范围 Operation Temperature:-10°C ~ +65°C



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G11025HA,S	Sleeve	100~125	50/60	0.2	18	2300/2900	35/41	84/100	49/59	1	/
G11025HA,S		200~240	50/60	0.1	18	2300/2900	35/41	84/100	49/59	1	/
G11025HA,B	Ball	100~125	50/60	0.2	18	2300/2900	35/41	84/100	49/59	1	/
G11025HA,B		200~240	50/60	0.1	18	2300/2900	35/41	84/100	49/59	1	/
G11025MA,S	Sleeve	100~125	50/60	0.16	16	1800/2300	30/35	70/84	41/49	1	/
G11025MA,S		200~240	50/60	0.8	16	1800/2300	30/35	70/84	41/49	1	/
G11025MA,B	Ball	100~125	50/60	0.16	16	1800/2300	30/35	70/84	41/49	1	/
G11025MA,B		200~240	50/60	0.8	16	1800/2300	30/35	70/84	41/49	1	/

