



尺寸 Size:120mmx120mmx25mm
 风量 Airflow:76~112m³/hr
 45~66CFM

重量 Weight:314g
 噪音 Noise:31~42dBA
 风叶 Impeller:PBT Thermoplastic Black,UL94-VO
 外框 Frame:Aluminum Alloy
 端子 Terminals: 0.5mm
 引线 Lead Wire:AWG#22 UL 1007
 (Optional)
 马达 Motor:Shaded Pole Induction Motor
 安规认证 Safety:UL>CUL>TUV>CE>CCC
 温度范围 Operation Temperature:-10℃ ~ +65℃

Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G12025HA,S	Sleeve	100~125	50/60	0.2	18	2300/2700	39/42	96/112	57/66	1	/
G12025HA,S		200~240	50/60	0.1	18	2300/2700	39/42	96/112	57/66	1	/
G12025HA,B	Ball	100~125	50/60	0.2	18	2300/2700	39/42	96/112	57/66	1	/
G12025HA,B		200~240	50/60	0.1	18	2300/2700	39/42	96/112	57/66	1	/
G12025MA,S	Sleeve	100~125	50/60	0.16	16	1800/2300	31/36	76/95	45/56	1	/
G12025MA,S		200~240	50/60	0.08	16	1800/2300	31/36	76/95	45/56	1	/
G12025MA,B	Ball	100~125	50/60	0.16	16	1800/2300	31/36	76/95	45/56	1	/
G12025MA,B		200~240	50/60	0.08	16	1800/2300	31/36	76/95	45/56	1	/

