

尺寸 Size: 120mmx120mmx38mm

风量 Airflow: 141~183m³/hr

83~108CFM

重量 Weight: 480g

噪音 Noise: 38~46dBA

风叶 Impeller: PBT Thermoplastic Black, UL94-V0

外框 Frame: Aluminum Alloy

端子 Terminals: 0.5mm


引线 Lead Wire: AWG#22 UL 1007

(Optional)

马达 Motor: Shaded Pole Induction Motor

安规认证 Safety: UL>CUL>TUV>CE>

温度范围 Operation Temperature: -10°C ~ +65°C



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G12038HA,S-7P	Sleeve	100~125	50/60	0.28	24	2400/2800	42/46	156/183	92/108	1	/
G12038HA,S-7P		200~240	50/60	0.14	24	2400/2800	42/46	156/183	92/108	1	/
G12038HA,B-7P	Ball	100~125	50/60	0.28	24	2400/2800	42/46	156/183	92/108	1	/
G12038HA,B-7P		200~240	50/60	0.14	24	2400/2800	42/46	156/183	92/108	1	/
G12038MA,S-7P	Sleeve	100~125	50/60	0.22	20	2100/2500	38/43	141/161	83/95	1	/
G12038MA,S-7P		200~240	50/60	0.11	20	2100/2500	38/43	141/161	83/95	1	/
G12038MA,B-7P	Ball	100~125	50/60	0.22	20	2100/2500	38/43	141/161	83/95	1	/
G12038MA,B-7P		200~240	50/60	0.11	20	2100/2500	38/43	141/161	83/95	1	/

