

尺寸 Size:135mmx135mmx38mm

风量 Airflow:141~205m³/hr
83~122CFM

重量 Weight:555g

噪音 Noise:41~53dBA

风叶 Impeller:PBT Thermoplastic Black ,UL94-VO

外框 Frame:Aluminum Alloy

端子 Terminals: 0.5mm


引线 Lead Wire:AWG#22 UL 1007

(Optional)

马达 Motor:Shaded Pole Induction Motor

安规认证 Safety:CE>Ⓢ

温度范围 Operation Temperature:-10°C ~ +65°C



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow(风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G13538HA,S	Sleeve	100~125	50/60	0.34	25	2400/2800	46/53	165/205	97/122	1	/
G13538HA ₂ S		200~240	50/60	0.18	25	2400/2800	46/53	165/205	97/122	1	/
G13538HA,B	Ball	100~125	50/60	0.34	25	2400/2800	46/53	165/205	97/122	1	/
G13538HA ₂ B		200~240	50/60	0.18	25	2400/2800	46/53	165/205	97/122	1	/
G13538MA,S	Sleeve	100~125	50/60	0.3	22	2100/2500	41/46	141/166	83/98	1	/
G13538MA ₂ S		200~240	50/60	0.16	22	2100/2500	41/46	141/166	83/98	1	/
G13538MA,B	Ball	100~125	50/60	0.3	22	2100/2500	41/46	141/166	83/98	1	/
G13538MA ₂ B		200~240	50/60	0.16	22	2100/2500	41/46	141/166	83/98	1	/

