


尺寸 Size:140mmx140mmx45mm
 风量 Airflow:265~355m³/hr
 156~209CFM

重量 Weight:805g
 噪音 Noise:44~56dBA
 风叶 Impeller:PBT Thermoplastic Black ,UL94-V0
 外框 Frame:Aluminum Alloy
 端子 Terminals: 0.5mm
 引线 Lead Wire:AWG#22 UL 1015
 (Optional)
 马达 Motor:Capacitor-Run Induction Motor
 安规认证 Safety:UL>CUL>TUV>CE>CCC
 温度范围 Operation Temperature:-10℃ ~ +70℃



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow(风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G14045HA,B	Ball	100~125	50/60	0.35	35	2700/3400	48/56	300/355	178/209	1	3.0uF/250v
G14045HA ₂ B	Ball	200~240	50/60	0.18	35	2700/3400	48/56	300/355	178/209	1	1.0uF/500v
G14045MA,B	Ball	100~125	50/60	0.28	28	2400/2800	44/50	265/310	156/182	1	3.0uF/250v
G14045MA ₂ B	Ball	200~240	50/60	0.14	28	2400/2800	44/50	265/310	156/182	1	1.0uF/500v

