


尺寸 Size:160mmx160mmx62mm
 风量 Airflow:373~501m³/hr
 220~295CFM

重量 Weight:1200g
 噪音 Noise:50~59dBA
 风叶 Impeller:PBT Thermoplastic Black ,UL94-V0
 外框 Frame:Aluminum Alloy
 端子 Terminals: 0.5mm
 引线 Lead Wire:AWG#22 UL 1015
 (Optional)
 马达 Motor:Capacitor-Run Induction Motor
 安规认证 Safety:UL>CUL>TUV>CE>CCC
 温度范围 Operation Temperature:-10°C ~ +65°C



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G16062HA,B	Ball	100~125	50/60	0.4	42	2600/3000	54/59	433/501	255/295	1	3.3uf/250v
G16062HA,B	Ball	200~240	50/60	0.2	42	2600/3000	54/59	433/501	255/295	1	0.68uf/500v
G16062MA,B	Ball	100~125	50/60	0.36	40	2300/2600	50/54	373/433	220/255	1	3.3uf/250v
G16062MA,B	Ball	200~240	50/60	0.19	40	2300/2600	50/54	373/433	220/255	1	0.68uf/500v

