



尺寸 Size:172mmx150mmx39mm
风量 Airflow:330~375m³/hr
194~220CFM

重量 Weight:655g
噪音 Noise:56~60dBA
风叶 Impeller:PBT Thermoplastic Black ,UL94-VO
外框 Frame:Aluminum Alloy
端子 Terminals: 0.5mm
引线 Lead Wire:AWG#22 UL 1015
(Optional)
马达 Motor:Capacitor-Run Induction Motor
安规认证 Safety:UL>CUL>TUV>CE>CCC
温度范围 Operation Temperature:-10°C ~ +70°C

Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	AirFlow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G1740HA,B	Ball	100~125	50/60	0.36	30	2600/3000	56/60	330/375	194/220	1	3.3uf/250v
G1740HA ₂ B	Ball	200~240	50/60	0.18	30	2600/3000	56/60	330/375	194/220	1	1.0uf/500v
G1740HA ₃ B	Ball	380~420	50/60	0.08	30	2600/3000	56/60	330/375	194/220	3	—
G1740HA ₄ B	Ball	380~420	50/60	0.10	30	2600/3000	56/60	330/375	194/220	1	0.47uf/630v

