


尺寸 Size:172mmx150mmx51mm  
 风量 Airflow:282~365m<sup>3</sup>/hr  
 166~215CFM

重量 Weight:870g  
 噪音 Noise:49~56dBA  
 风叶 Impeller:PBT Thermoplastic Black ,UL94-V0  
 外框 Frame:Aluminum Alloy  
 端子 Terminals: 0.5mm  
 引线 Lead Wire:AWG#22 UL 1015  
 (Optional)  
 马达 Motor:Shaded Pole Induction Motor  
 安规认证 Safety:UL>CUL>TUV>CE>Ⓢ  
 温度范围 Operation Temperature:-10°C ~ +65°C



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G1750HA,S-7P	Sleeve	100~125	50/60	0.4	40	2500/2800	52/56	326/365	192/215	1	/
G1750HA,S-7P		200~240	50/60	0.22	40	2500/2800	52/56	326/365	192/215	1	/
G1750HA,B-7P	Ball	100~125	50/60	0.4	40	2500/2800	52/56	326/365	192/215	1	/
G1750HA,B-7P		200~240	50/60	0.22	40	2500/2800	52/56	326/365	192/215	1	/
G1750MA,S-7P	Sleeve	100~125	50/60	0.35	37	2200/2500	49/53	282/326	166/192	1	/
G1750MA,S-7P		200~240	50/60	0.19	37	2200/2500	49/53	282/326	166/192	1	/
G1750MA,B-7P	Ball	100~125	50/60	0.35	37	2200/2500	49/53	282/326	166/192	1	/
G1750MA,B-7P		200~240	50/60	0.19	37	2200/2500	49/53	282/326	166/192	1	/

