




尺寸 Size:172mmx150mmx51mm
 风量 Airflow:331~435m³/hr
 195~256CFM

重量 Weight:870g
 噪音 Noise:50~58dBA
 风叶 Impeller:PBT Thermoplastic Black ,UL94-V0
 外框 Frame:Aluminum Alloy
 端子 Terminals: 0.5mm
 引线 Lead Wire:AWG#22 UL 1015
 (Optional)
 马达 Motor:Capacitor-Run Induction Motor
 安规认证 Safety:UL>CUL>TUV>CE>CCC
 温度范围 Operation Temperature:-10°C ~ +65°C



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow(风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G1750HA,B-7P	Ball	100~125	50/60	0.4	42	2600/3000	53/58	374/435	220/256	1	3.3uf/250v
G1750HA ₂ ,B-7P	Ball	200~240	50/60	0.22	42	2600/3000	53/58	374/435	220/256	1	0.68uf/500v
G1750MA,B-7P	Ball	100~125	50/60	0.36	38	2300/2600	50/54	331/374	195/220	1	3.3uf/250v
G1750MA ₂ ,B-7P	Ball	200~240	50/60	0.19	38	2300/2600	50/54	331/374	195/220	1	0.68uf/330v



Key
 — 60Hz
 — 50Hz