



尺寸 Size:172mmx150mmx51mm
 风量 Airflow:319~399m³/hr
 188~235CFM

重量 Weight:870g
 噪音 Noise:52~62dBA
 风叶 Impeller:PBT Thermoplastic Black,UL94-V0
 外框 Frame:Aluminum Alloy
 端子 Terminals: 0.5mm
 引线 Lead Wire:AWG#22 UL 1015
 (Optional)
 马达 Motor:Capacitor-Run Induction Motor
 安规认证 Safety:UL>CUL>TUV>CE>CCC
 温度范围 Operation Temperature:-10°C ~ +65°C

| Model (型号) | Bearing System (轴承型式) | voltage VAC (电压) | Freq. Hz (频率) | Current A (电流) | Power W (功率) | Speed RPM (转速) | Noise dBA (噪音) | Air Flow (风量) | | Phase (相数) | Capacitor (电容) |
|---------------|--------------------------|------------------------|---------------------|----------------------|--------------------|----------------------|----------------------|---------------|---------|---------------|-------------------|
| | | | | | | | | M3/hr | CFM | | |
| G1750HA,B | Ball | 100~125 | 50/60 | 0.38 | 40 | 2700/3100 | 57/62 | 348/399 | 205/235 | 1 | 3.3uf/250v |
| G1750HA,B | Ball | 200~240 | 50/60 | 0.2 | 40 | 2700/3100 | 57/62 | 348/399 | 205/235 | 1 | 0.68uf/500v |
| G1750MA,B | Ball | 100~125 | 50/60 | 0.32 | 36 | 2300/2700 | 52/57 | 319/348 | 188/205 | 1 | 3.3uf/250v |
| G1750MA,B | Ball | 200~240 | 50/60 | 0.17 | 36 | 2300/2700 | 52/57 | 319/348 | 188/205 | 1 | 0.68uf/500v |



Key
 — 60Hz
 — 50Hz