



尺寸 Size:80mmx80mmx25mm

风量 Airflow:24~39m³/hr
14~23CFM

重量 Weight:208g

噪音 Noise:22~30dBA

风叶 Impeller:PBT Thermoplastic Black, UL94-VO

外框 Frame: Aluminum Alloy

端子 Terminals: 0.5mm

引线 Lead Wire:AWG#22 UL 1007

(Optional)

马达 Motor:Shaded Pole Induction Motor

安规认证 Safety:UL>CUL>TUV>CE>Ⓢ

温度范围 Operation Temperature:-10°C ~ +65°C

Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	AirFlow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G8025HA,S	Sleeve	100~125	50/60	0.13	13	2300/2700	27/30	32/39	19/23	1	/
G8025HA,S		200~240	50/60	0.07	13	2300/2700	27/30	32/39	19/23	1	/
G8025HA,B	Ball	100~125	50/60	0.13	13	2300/2700	27/30	32/39	19/23	1	/
G8025HA,B		200~240	50/60	0.07	13	2300/2700	27/30	32/39	19/23	1	/
G8025MA,S	Sleeve	100~125	50/60	0.13	13	1700/2200	22/26	24/32	14/19	1	/
G8025MA,S		200~240	50/60	0.07	13	1700/2200	22/26	24/32	14/19	1	/
G8025MA,B	Ball	100~125	50/60	0.13	13	1700/2200	22/26	24/32	14/19	1	/
G8025MA,B		200~240	50/60	0.07	13	1700/2200	22/26	24/32	14/19	1	/

