

尺寸 Size:80mmx80mmx38mm

风量 Airflow:36~48m³/hr
21~28CFM

重量 Weight:310g

噪音 Noise:26~33dBA

风叶 Impeller:PBT Thermoplastic Black,UL94-VO

外框 Frame:Aluminum Alloy

端子 Terminals: 0.5mm


引线 Lead Wire:AWG#22 UL 1007

(Optional)

马达 Motor:Shaded Pole Induction Motor

安规认证 Safety:UL>CUL>TUV>CE>CCC

温度范围 Operation Temperature:-10°C ~ +65°C



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G8038HA,S	Sleeve	100~125	50/60	0.14	14	2400/2900	28/33	39/48	23/28	1	/
G8038HA,S		200~240	50/60	0.07	14	2400/2900	28/33	39/48	23/28	1	/
G8038HA,B	Ball	100~125	50/60	0.14	14	2400/2900	28/33	39/48	23/28	1	/
G8038HA,B		200~240	50/60	0.07	14	2400/2900	28/33	39/48	23/28	1	/
G8038MA,S	Sleeve	100~125	50/60	0.13	13	2300/2700	26/31	36/44	21/26	1	/
G8038MA,S		200~240	50/60	0.06	13	2300/2700	26/31	36/44	21/26	1	/
G8038MA,B	Ball	100~125	50/60	0.13	13	2300/2700	26/31	36/44	21/26	1	/
G8038MA,B		200~240	50/60	0.06	13	2300/2700	26/31	36/44	21/26	1	/

