




尺寸 Size:127mmx127mmx38mm  
风量 Airflow:180~248m<sup>3</sup>/hr  
106~146CFM

重量 Weight:670g  
噪音 Noise:42~52dBA  
风叶 Impeller:Iron Leaf  
外框 Frame:Aluminum Alloy  
端子 Terminals: 0.5mm  
引线 Lead Wire:The Mostable Wire  
(Optional)  
马达 Motor:Shaded Pole External Rotor  
Induction Motor  
安规认证 Safety:UL>CUL>TUV>CE>CCC  
温度范围 Operation Temperature:-10℃ ~ +105℃



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	AirFlow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
TG12738HA,S-7P	Sleeve	100~125	50/60	0.3	27	2600/3000	46/52	224/248	132/146	1	/
TG12738HA,S-7P		200~240	50/60	0.18	25	2600/3000	46/52	224/248	132/146	1	/
TG12738HA,B-7P	Ball	100~125	50/60	0.3	27	2600/3000	46/52	224/248	132/146	1	/
TG12738HA,B-7P		200~240	50/60	0.18	25	2600/3000	46/52	224/248	132/146	1	/
TG12738MA,S-7P	Sleeve	100~125	50/60	0.28	25	2000/2200	42/44	180/195	106/114	1	/
TG12738MA,S-7P		200~240	50/60	0.16	23	2000/2200	42/44	180/195	106/114	1	/
TG12738MA,B-7P	Ball	100~125	50/60	0.28	25	2000/2200	42/44	180/195	106/114	1	/
TG12738MA,B-7P		200~240	50/60	0.16	23	2000/2200	42/44	180/195	106/114	1	/



Key  
60Hz  
50Hz