

尺寸 Size: 127mmx127mmx38mm
风量 Airflow: 160~227m³/hr
94~134CFM

重量 Weight: 650g

噪音 Noise: 41~55dBA

风叶 Impeller: Iron Leaf

外框 Frame: Aluminum Alloy

端子 Terminals: 0.5mm


引线 Lead Wire: The Mostable Wire
(Optional)

马达 Motor: Shaded Pole External Rotor



Induction Motor

安规认证 Safety: UL>CUL>TUV>CE>®

温度范围 Operation Temperature: -10°C ~ +105°C



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
TG12738HA,S	Sleeve	100~125	50/60	0.28	27	2600/3000	50/55	204/227	120/134	1	—
TG12738HA,S		200~240	50/60	0.16	25	2600/3000	50/55	204/227	120/134	1	—
TG12738HA,B	Ball	100~125	50/60	0.28	27	2600/3000	50/55	204/227	120/134	1	—
TG12738HA,B		200~240	50/60	0.16	25	2600/3000	50/55	204/227	120/134	1	—
TG12738MA,S	Sleeve	100~125	50/60	0.26	25	2000/2200	41/45	160/178	94/105	1	—
TG12738MA,S		200~240	50/60	0.15	23	2000/2200	41/45	160/178	94/105	1	—
TG12738MA,B	Ball	100~125	50/60	0.26	25	2000/2200	41/45	160/178	94/105	1	—
TG12738MA,B		200~240	50/60	0.15	23	2000/2200	41/45	160/178	94/105	1	—



Key
— 60Hz
— 50Hz