

尺寸 Size:280mmx280mmx80mm
 风量 Airflow:2280~2570m³/hr
 1341~1512CFM

重量 Weight:2800g

噪音 Noise:65~70dBA

风叶 Impeller:Iron Leaf


外框 Frame:Aluminum Alloy

引线 Lead Wire:The Mostable Wire

马达 Motor:Capacitor-Run External Rotor
 Induction Motor

安规认证 Safety:UL>CUL>TUV>CE>CCC

温度范围 Operation Temperature:-10°C ~ +105°C



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
TG28080HA ₁	Ball	100~125	50/60	1.2	120	2400/2650	65/70	2280/2570	1341/1512	1	4.0uf/250v
TG28080HA ₂	Ball	200~240	50/60	0.55	120	2400/2650	65/70	2280/2570	1341/1512	1	2.0uf/500v
TG28080HA ₃	Ball	380~420	50/60	0.32	120	2400/2650	65/70	2280/2570	1341/1512	3	—
TG28080HA ₄	Ball	380~420	50/60	0.36	120	2400/2650	65/70	2280/2570	1341/1512	1	2.0uf/500v

