





尺寸 Size:92mmx92mmx38mm  
 风量 Airflow:71~91m<sup>3</sup>/hr  
 42~54CFM

重量 Weight:480g  
 噪音 Noise:35~43dBA  
 风叶 Impeller:Iron Leaf  
 外框 Frame:Aluminum Alloy  
 端子 Terminals: 0.5mm  
 引线 Lead Wire:The Mostable Wire  
 (Optional)  
 马达 Motor:Shaded Pole External Rotor  
 Induction Motor

安规认证 Safety:UL>CUL>TUV>CE>Ⓢ  
 温度范围 Operation Temperature:-10°C ~ +105°C



Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
TG9238HA,S	Sleeve	100~125	50/60	0.24	16	2600/3000	38/43	78/91	46/54	1	/
TG9238HA,S		200~240	50/60	0.12	16	2600/3000	38/43	78/91	46/54	1	/
TG9238HA,B	Ball	100~125	50/60	0.24	16	2600/3000	38/43	78/91	46/54	1	/
TG9238HA,B		200~240	50/60	0.12	16	2600/3000	38/43	78/91	46/54	1	/
TG9238MA,S	Sleeve	100~125	50/60	0.22	14	2300/2700	35/40	71/85	42/50	1	/
TG9238MA,S		200~240	50/60	0.10	14	2300/2700	35/40	71/85	42/50	1	/
TG9238MA,B	Ball	100~125	50/60	0.22	14	2300/2700	35/40	71/85	42/50	1	/
TG9238MA,B		200~240	50/60	0.10	14	2300/2700	35/40	71/85	42/50	1	/



Key  
 — 60Hz  
 — 50Hz