



尺寸 Size:210mmx210mmx70mm

风量 Airflow:780~900m³/hr

459~529CFM

重量 Weight:1700g

噪音 Noise:70~75dBA

风叶 Impeller:PA6 UL94V-0 Reinforcee Plastic

外框 Frame:Aluminum Alloy

引线 Lead Wire:AWG#22 UL 1015

马达 Motor:Capacitor-Run Induction Motor

安规认证 Safety:CE>

温度范围 Operation Temperature:-10°C ~ +65°C

Model (型号)	Bearing System (轴承型式)	voltage VAC (电压)	Freq. Hz (频率)	Current A (电流)	Power W (功率)	Speed RPM (转速)	Noise dBA (噪音)	Air Flow (风量)		Phase (相数)	Capacitor (电容)
								M3/hr	CFM		
G21070HA ₁	Ball	100~125	50/60	0.6	65	2800/3000	70/75	780/900	459/529	1	3.0uf/250v
G21070HA ₂	Ball	200~240	50/60	0.3	65	2800/3000	70/75	780/900	459/529	1	1.0uf/500v
G21070HA ₃	Ball	380~420	50/60	0.15	65	2800/3000	70/75	780/900	459/529	3	
G21070HA ₄	Ball	380~420	50/60	0.16	65	2500/3000	70/75	780/900	459/529	1	1.0uf/630v

